

SCENICVIEW P15-1 15-inch Premium Line LCD TFT Display



Picture similar

premium



The SCENICVIEW P15-1 combines fantastic design with perfect ergonomics and improved usability.

Discover the powerful functionality of the new Premium Line Displays. LCD TFT technology stands for top-quality picture, ergonomics and ideal environment compatibility. The highly flexible Premium stand guarantees optimised individual solutions for any workplace environment. With its integrated speakers, the SCENICVIEW P15-1 is the ideal choice for modern PC applications. Don't be satisfied with less.

- 15-inch LCD TFT display (comparable with 17-inch CRT)
- Recommended resolution 1024 x 768 pixels
- 16.7 million colors
- Integrated audio
- Integrated power supply
- Tilt-and-swivel base with height-adjust and 90° rotation (portrait function)
- Pivot®Pro software included
- Ease-of-use OSD menu
- DVI-D and analog interface
- Optimum ergonomics ISO 13406-2 flicker-free and distortion-free
- Excellent focus and high contrast
- Low power consumption
- Multi-level power management EPA, VESA DPMS
- Plug & Play VESA DDC 2B device
- Low-radiation and environmental friendly according to TCO'99
- Immune to external electromagnetic fields
- Auto-adjust
- Mechanical interface standardised according to VESA FPMPI (75 mm)
- sRGB

Data Sheet

Visible screen diagonal	15 inch (38 cm)
Graphics display (dependent on graphics processor)	
Pixels	1024 x 768
Pixels *)	800 x 600
Pixels *)	640 x 480
*) expanded	
Text display (dependent on graphics processor)	
Pixels (max. 75 Hz)	720 x 400
Picture size	304 x 228 mm
Pixel Pitch	0.297 mm
Frequencies	
Horizontal	30 - 60 kHz
Vertical	55 - 75 Hz
Brightness typical	300 cd/m ²
Contrast typical	450 : 1
Viewing angle typical	
Horizontal	150°
Vertical	110°
Response time typical	25 ms
Plug & Play	VESA DDC 2B
Ease-of-use menu	
Direct key access	auto adjust, mute, brightness menu
Brightness / contrast	brightness, contrast, black level, auto level
Image adjust	H, V position, clock, phase
Audio	volume, mute
Color	sRGB, 6500 K, 7500 K, 9300 K, native, customer settings
OSD setup	language, position, timeout, rotation
Advanced	input select, resolution notifier, factory recall
Information	
Tilt-and-swivel base	
Tilt angle	-5° / +15°
Swivel angle	+45° / -45°
Height-adjust range	50 mm
Audio characteristics	
Volume control	digital
Audio signal input (from PC)	3.5 mm stereo phone jack
Sound output	1,5 W (L) + 1,5 W (R)

Electrical values	
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw typical	
Operation (w/o sound)	30 W
Standby mode	1 W
Suspend mode	1 W
Off mode	< 1 W
Protection class	1
Temperatures / dimensions / weight	
Ambient temperature (to IEC721)	
Recommended range	15°C to 32°C
Limit	0°C to 35°C
Dimensions (landscape, lowest position)	
(H x W x D)	388 x 354 x 215 mm
Weight unpacked / packed	4.6 kg / 6.3 kg
Reliability typical	
MTBF (demonstrated)	70,000 h
Lifetime of LCD	50,000 h
(brightness > 50 % of original brightness)	
Compliance with standards	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'99
Video input	1 x D-SUB analog 1 x DVI-D digital
Data cable (1.8 m)	D-SUB (15-pin) analog detachable on display DVI-D (24-pin) digital audio cable (1.8 m)
Power cable (1.8 m)	for connection to PC outlet
Integrated power supply	
Plug type on display side	IEC-320-C13
Special features	Kensington Lock prepared, standardized mounting interface according VESA FPMPI (75mm), stand with 90° - rotation Pivot®Pro software included
Order code	S26361-K902-V150



Published by Fujitsu Siemens Computers http://www.fujitsu-siemens.com/	All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners. Copyright © Fujitsu Siemens Computers, 05/2002	Company stamp
---	---	----------------------